

RUGGEDBILT TRAILERS

Heavy Duty 10 Ton Gooseneck



Standard Features

- 20,000 lb. G.V.W.R.
- 10,000 lb. x 2 G.A.W.R.
- 2 5/16" Bulldog Gooseneck Ball Coupler (25K)
- Safety Chains
- 2 - Bulldog Drop Leg Jacks (12K) Single Speed
- 2 - Dexter Oil Bath Brake Axles (10,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 8 - 16" Grey Dual Wheels
- 8 - 16" 235/80R16 Radial Tires
- Rubrail & Stake Pockets with Chain Sliders
- Electric Breakaway Kit w/ Charger
- Side Steps on Both Sides
- Heat Shrink Wiring Connection
- Storage Toolbox Between Neck Uprights
- 5' Dovetail with (2) Flip Over Spring Assisted Leveling Ramps
- 12" x 19 lb. I-Beam Main Frame
- 10" x 15 lb. I-Beam Neck
- 3" Channel Crossmembers 16" on Center
- 5 x 3 x 1/4" Angle Outer Deck Frame
- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- DOT Approved Lighting
- Amber Side Turn Flashers
- Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated

Model	Deck Length	GVWR	Weight	
10TGN20-5	20'+5'	20000		
10TGN22-5	22'+5'	20000		
10TGN23-5	23'+5'	20000		
10TGN25-5	25'+5'	20000		

10 Ton Heavy Duty Gooseneck Options

Part #	Description	
STW2358516	Tire, Spare 235/85/R16	
STM	Spare Tire Mount	
RBGN3RDR	Ramps, 3rd Spring Assist	
RBGNPUD	Dovetail, Pop Up	
RBSMTB	Box, 18"x18"x24" Tool	
RBGN2SJ	Jack, Two Speed	
RBPH	Neck, Pintle Hitch	
RBGN6T	Neck, 6" Taller Gooseneck	
RBGND	Deck, 102"x6' Over Neck	
RBGNDR	D-Ring	
RBGNPB	Frame, Pierce Beam	



Gooseneck Side Step



Gooseneck Spring Assisted Ramps

