

# RUGGEDBILT TRAILERS

## 72 Model Dump Trailer



### Standard Features

- 2 5/16" A-Frame Ball Coupler
  - Safety Chains
  - 1 - Drop Leg Jack (7K & 10K)
  - 2 - Dexter E-Z Lube Brake Axles (3.5K, 5.2K, 6K, 7K)
  - Electric Breakaway Kit w/ Charger
  - 7-Way RV Plug
  - Heat Shrink Wiring Connection
  - On Board Power Up/Down Hydraulic System
  - On Board 110VAC to 12VDC Battery Charger
  - Wireless Controls
  - 11 Ga. Sides 24" Tall
  - 11 Ga. Steel Floor
  - 45 Degree Dump Angle
  - Gate, Double Swing (Spreader & Barn Style)
  - Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated
- Tires
- 4 - 205/75R15 Tires (3.5 Ton)
  - 4 - 225/75R15 Tires (5 Ton)
  - 4 - 235/85R16 Tires (6 Ton)
  - 4 - 235/80R16 Tires (7 Ton)
- Wheels
- 4 - 15" White Spoke Wheels (3.5 & 5 Ton)
  - 4 - 16" White Spoke Wheels (6 & 7 Ton)

Model	Size	Cylinders	G.V.W.R.		
3.5TD7210	72" x 10'	Single	7,000 Lbs.		
5TD7210	72" x 10'	Single	10,000 Lbs.		
5TD7212	72" x 12'	Dual	10,000 Lbs.		
6TD7210	72" x 10'	Dual	12,000 Lbs.		
6TD7212	72" x 12'	Dual	12,000 Lbs.		
7TD7212	72" x 12'	Dual	14,000 Lbs.		

### 72 Model Dump Trailer Options

Part #	Description	
STW2057515	Tire, Spare 205/75/R15 (3.5 Ton)	
STW2257515	Tire, Spare 225/75/R15 (5 Ton)	
STW2358516	Tire, Spare 235/85/R16 (6 Ton)	
STW2358016	Tire, Spare 235/80/R16 (7 Ton)	
STM	Spare Tire Mount	
72FTPTD	Fender, Tread Plate Tear Drop	
72HDSSR	Ramps, 6' Heavy Duty (Self Store)	
AC2516	Coupler, 2-5/16" Adjustable	
BAC2516	Coupler, Bulldog 2-5/16" Adjustable	
PAC2516	Coupler, Adjustable Pintle Ring	
GN2516	Gooseneck, 2-5/16 Adjustable	
72SL	Scissor Lift Upgrade from Dual Cylinders	



