

RUGGEDBILT TRAILERS

Medium Duty 7 Ton Gooseneck



Standard Features

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- 2 5/16" Bulldog Gooseneck Ball Coupler (25K)
- Safety Chains
- 1 - Bulldog Drop Leg Jacks (12K) Single Speed
- 2 - Dexter E-Z Lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires
- Rubrail & Stake Pockets with Chain Sliders
- Electric Breakaway Kit w/ Charger
- Side Steps on Both Sides
- Storage Basket Between Neck Uprights
- 5' Dovetail with Flip up Ramps
- 10" x 15 lb. I-Beam Main Frame
- 10" x 12 lb. I-Beam Neck
- 3" Channel Crossmembers 24" on Center
- 5 x 3 x 1/4" Angle Outer Deck Frame
- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- Heat Shrink Wiring Connection
- Amber Side Turn Flashers
- Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated

Model	Deck Length	GVWR	Weight	
7TGN20-5	20'+5'	14000		
7TGN22-5	22'+5'	14000		
7TGN23-5	23'+5'	14000		
7TGN25-5	25'+5'	14000		

7 Ton Medium Duty Gooseneck Options

Part #	Description	
STW2358016	Tire, Spare 235/80/R16	
STM	Spare Tire Mount	
RBSMTB	Box, 18"x18"x24" Tool	
RBPH	Neck, Pintle Hitch	
RBGN6T	Neck, 6" Taller Gooseneck	
RBGND	Deck, 102"x6' Over Neck	
RBGNDR	D-Ring	
RBGNPB	Frame, Pierce Beam	



Gooseneck Side Step



Gooseneck Spring Assisted Ramps

