

# RUGGEDBILT TRAILERS

## 82 Model Dump Trailer



### Standard Features

- 2 5/16" Adjustable Ball Coupler
  - Safety Chains
  - 1 - Drop Leg Jack (7K & 10K)
  - 2 - Dexter E-Z Lube Brake Axles (5.2K, 6K, 7K)
- Wheels
- 4 - 15" White Spoke Wheels (5 Ton)
  - 4 - 16" White Spoke Wheels (6 & 7 Ton) - 8 Lug
- Tires
- 4 - 225/75R15 Tires (5 Ton)
  - 4 - 235/85R16 Tires (6 Ton)
  - 4 - 235/80R16 Tires (7 Ton)
- DOT Reflective Lighting & Tap
  - 7-Way RV Plug
  - Electric Breakaway Kit w/ Charger
  - On Board Power Up/Down Hydraulic System
  - On Board 110VAC to 12VDC Battery Charger
  - Wireless Controls
  - Dual Cylinders
  - 11 Ga. Sides 24" Tall
  - 7 Ga. (3/16") Steel Floor
  - 45 Degree Dump Angle
  - Ramps, 6' Heavy Duty Self Store (Underneath)
  - Gate, Double Swing (Spreader & Barn Style)
  - D-Ring (4) In Bed
  - Deburred and Hand Prepped, Acid Washed
  - Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated
  - Heat Shrink Wiring Connection

Model	Size	G.V.W.R.	Weight
5TD8210	82" x 10'	10,000 Lbs.	
5TD8212	82" x 12'	10,000 Lbs.	
6TD8210	82" x 10'	12,000 Lbs.	
6TD8212	82" x 12'	12,000 Lbs.	
7TD8212	82" x 12'	14,000 Lbs.	
7TD8214	82" x 14'	14,000 Lbs.	
7TD8216	82" x 16'	14,000 Lbs.	



Spreader Gate



Heavy Duty Ramps



Barn Doors

### 82 Model Dump Trailer Options

Part #	Description	
STW2257515	Tire, Spare 225/75/R15 (5 Ton)	
STW2358516	Tire, Spare 235/85/R16 (6 Ton)	
STW2358016	Tire, Spare 235/80/R16 (7 Ton)	
STM	Spare Tire Mount	
72FTPTD	Fender, Tread Plate Tear Drop	
PAC2516	Coupler, Adjustable Pintle Ring	
GN2516	Gooseneck, 2-5/16 Adjustable	
72SL	Scissor Lift Upgrade	
RBDTARP	Top Roller Kit w/ Hand Crank	

