

RUGGEDBILT TRAILERS

Gravity Tilt Trailer



Model: GTH8216 Shown with a 4' Stationary Option

Standard Features

- 2 5/16" Adjustable Ball Coupler
- Safety Chains
- 1 - Drop Leg Jack (7 Ton -10K) (5 Ton - 7K)
- 2 - Dexter E-Z Lube Brake Axles (5.2K) Brakes on Both
- 2 - Dexter E-Z Lube Brake Axles (7K) Brakes on Both

Wheels


- 4 - 16" White Spoke Wheels (7 & 6 Ton)
- 4 - 15" White Spoke Wheels (5 Ton)

Tires

- 4 - 235/80R16 Tires (7 & 6 Ton)
- 4 - 225/75R15 Tires (5 Ton)

- Heat Shrink Wiring Connection
- Electric Breakaway Kit w/ Charger
- DOT Reflective Lighting & Tape
- Variable Rate Control Valve
- Single 3"x16" Cylinder
- Stake Pockets and Rub Rail
- 6" Channel Frame and Wrap Tongue
- 3" Channel Crossmembers on 16" Centers
- 2" Pressure Treated Pine Floor
- 9"x72" Treadplate Removeable Fenders
- Deburred and Hand Prepped, Acid Washed
- Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated

Model	Size	G.V.W.R.	Weight	
GT8216	82" x 16'	10,000 Lbs.		
GT8218	82" x 18'	10,000 Lbs.		
GTM8216	82" x 16'	12,000 Lbs.		
GTM8218	82" x 18'	12,000 Lbs.		
GTH8216	82" x 16'	14,000 Lbs.		
GTH8218	82" x 18'	14,000 Lbs.		



Removeable Fenders



4' Stationary (Option)



Low Load Angle Approach

Tilt Trailer Options

Part #	Description	
STW2358016	Tire, Spare 235/80/R16 (7 Ton)	
STW2257515	Tire, Spare 225/75/R15 (5 Ton)	
STM	Spare Tire Mount	
RBTEL	Length, Extra Stationary Deck per 2ft	
RBSF	Floor, Diamond Plate 1/8" Thick	
RBBD2516	Coupler, Bulldog Adjustable 2-5/16"	
RBTGN	Gooseneck, 2-5/16 Adjustable	

