

RUGGEDBILT TRAILERS

Single Axle Utility



Trailer shown with Ramp Gate Option

Standard Features

- 3,500 lb. G.V.W.R.
- 3,500 lb. x 1 G.A.W.R.
- 2" A-Frame Coupler
- Safety Chains
- 1 - 2K Swivel Jack
- 1 - Dexter EZ Lube Axle
- Spring Suspension
- 2 - 15" White Spoke Wheels
- 2 - 15" 205/75D15 Tires
- 3-1/2"x2-1/2"x3/16" Angle Tongue
- 3"x2"x3/16" Angle Main Frame
- 3"x2"x3/16" Angle Crossmembers
- Treated Pine Lumber Deck
- Heat Shrink Wiring Connection
- Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated

Model	Size	GVWR	Weight	
SA6008	60" x 8'	2995		
SA6010	60" x 10'	2995		
SA6012	60" x 12'	2995		
SA6014	60" x 14'	2995		
SA7710	77" x 10'	2995		
SA7712	77" x 12'	2995		
SA7714	77" x 14'	2995		

Single Axle Utility Options

Part #	Description	
RBRG564	Gate, 4' Mesh Gate 56"	
RBRG565	Gate, 5' Mesh Gate 56"	
RBRG664	Gate, 4' Mesh Gate 60" & 66"	
RBRG665	Gate, 5' Mesh Gate 60" & 66"	
STW2057515	Tire, Spare 205/75/D15 (3.5 Ton)	
USTM	Utility Spare Tire Mount	
AFC2BD	Coupler, 2" Bulldog	
RBULED	Lights, LED Upgrade	
RBSP	Stake Pockets Each	
RBSAMF	Floor, Mesh Per Linear Feet	
RB5RSS	Ramps, 5' Self Store	
RBSAWT	Tongue, Wrap Around Tongue	

77" wide trailer options

RBRG774	Gate, 4' Mesh Gate 77"	
RBRG775	Gate, 5' Mesh Gate 77"	
RB5RSS	Ramps, 5' Self Store	
RBATV	Ramps, ATV Package	
AFC2516BD	Coupler, 2-5/16" Bulldog	
RBSAWT	Tongue, Wrap Around Tongue	

