

RUGGEDBILT TRAILERS

Tandem Axle Flatbed



Trailer Shown with Ramp Gate Option

Standard Features

- 7,000 lb. G.V.W.R.
- 3,500 lb. x 2 G.A.W.R.
- 2-5/16" A-Frame Coupler
- Safety Chains
- 1 - 2K Swivel Jack
- 2 - Dexter EZ Lube Axles (1) Electric Brake
- Spring Suspension
- 4 - 15" White Spoke Wheels
- 4 - 15" 205/75D15 Tires
- Electric Breakaway Kit w/ Charger
- 4" Channel Wrap Around Tongue
- 5"x3"x1/4" Angle Main Frame
- 3"x2"x3/16" Angle Crossmembers
- 2" Treated Pine Lumber Deck
- Electric Breakaway Kit w/ Charger
- Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated
- Heat Shrink Wiring Connection

Model	Size	GVWR	Weight	
FB7712	77" x 12'	7000		
FB7714	77" x 14'	7000		
FB7716	77" x 16'	7000		
FB7718	77" x 18'	7000		
FB7720	77" x 20'	7000		

Tandem Axle Flatbed Options

Part #	Description		
RBRG774	Gate, 4' Mesh Gate 77"		
RBRG775	Gate, 5' Mesh Gate 77"		
RB5RSS	Ramps, 5' Self Store		
RBATV	Ramps, ATV Package		
STW2057515	Tire, Spare 205/75/R15		
USTM	Utility Spare Tire Mount		
AFC2BD	Coupler, 2" Bulldog		
RBULED	Lights, LED Upgrade		
RBSP	Stake Pockets Each		
RBSAMF	Floor, Mesh Per Linear Feet		
RBFS	Floor, Diamond Plate 1/8" Thick		
RBTFD	Fender, Smooth Tear Drop		
RBSURHD	Ramps, 5' Stand Up Heavy Duty		
RBSAWT	Tongue, Wrap Around Tongue		
RBTAGN	Gooseneck, Adjustable 2-5/16"		

Prices effective 7/1/10

Prices and specifications subject to change without notice.

