

RUGGEDBILT TRAILERS

Tandem Axle Heavy Utility



Shown with Ramp Gate Option

Standard Features				
<ul style="list-style-type: none"> • 10,400 lb. G.V.W.R. • 5,200 lb. x 2 G.A.W.R. • 2-5/16" A-Frame Coupler • Safety Chains • 2 - Dexter EZ Lube Axles (1) Electric Brake • Spring Suspension • 4 - 15" White Spoke Wheels • 4 - 15" 225/75D15 Tires 	<ul style="list-style-type: none"> • Electric Breakaway Kit w/ Charger • 5" Channel Wrap Around Tongue • 5"x3"x1/4" Angle Main Frame • 3"x2"x3/16" Angle Crossmembers • 2" Treated Pine Lumber Deck • Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated • Heat Shrink Wiring Connection • 1 - 7K Set Back 			
Model	Size	GVWR	Weight	
TAH7712	77" x 12'	10000		
TAH7714	77" x 14'	10000		
TAH7716	77" x 16'	10000		
TAH7718	77" x 18'	10000		
TAH7720	77" x 20'	10000		

Tandem Axle Heavy Utility Options

Part #	Description	
RBRG774	Gate, 4' Mesh Gate 77"	
RBRG775	Gate, 5' Mesh Gate 77"	
RB5RSS	Ramps, 5' Self Store	
RBATV	Ramps, ATV Package	
STW2257515	Tire, Spare 225/75/D15	
USTM	Utility Spare Tire Mount	
AFC2516BD	Coupler, 2-5/16" Bulldog	
RBULED	Lights, LED Upgrade	
RBSP	Stake Pockets Each	
RBSAMF	Floor, Mesh Per Linear Feet	
RBFS	Floor, Diamond Plate 1/8" Thick	
RBTDF	Fender, Smooth Tear Drop	
RB5RSS	Ramps, 5' Self Store	
RBSURHD	Ramps, 5' Stand Up Heavy Duty	
RBEB52K	Brake, Double Electric 10K	
RBTAGN	Gooseneck, Adjustable 2-5/16"	

Prices effective 7/1/10

Prices and specifications subject to change without notice.

