

RUGGEDBILT TRAILERS

Tandem Axle Utility



Shown with Ramp Gate Option

Standard Features

- 7,000 lb. G.V.W.R.
- 3,500 lb. x 2 G.A.W.R.
- 2-5/16" A-Frame Coupler
- Safety Chains
- 1 - 2K Swivel Jack
- 2 - Dexter EZ Lube Axles (1) Electric Brake
- Spring Suspension
- 4 - 15" White Spoke Wheels
- 4 - 15" 205/75/D15 Tires
- 4" Channel Tongue
- 3"x2"x3/16" Angle Main Frame
- 3"x2"x3/16" Angle Crossmembers
- 2" Treated Pine Lumber Deck
- Electric Breakaway Kit w/ Charger
- Electrostatic, Epoxy Primed and Poly-Urythaned Top Coated
- Heat Shrink Wiring Connection

Model	Size	GVWR	Weight	
TA7712	77" x 12'	7000		
TA7714	77" x 14'	7000		
TA7716	77" x 16'	7000		
TA7718	77" x 18'	7000		
TA7720	77" x 20'	7000		

Tandem Axle Utility Options

Part #	Description	
RBRG774	Gate, 4' Mesh Gate 77"	
RBRG775	Gate, 5' Mesh Gate 77"	
RB5RSS	Ramps, 5' Self Store	
RBATV	Ramps, ATV Package	
STW2057515	Tire, Spare 205/75/D15	
USTM	Utility Spare Tire Mount	
AFC2BD	Coupler, 2-5/16" Bulldog	
RBULED	Lights, LED Upgrade	
RBSP	Stake Pockets Each	
RBSAMF	Floor, Mesh Per Linear Feet	
RBFS	Floor, Diamond Plate 1/8" Thick	
RBTFD	Fender, Smooth Tear Drop	
RB5RSS	Ramps, 5' Self Store	
RBSURHD	Ramps, 5' Stand Up Heavy Duty	
RBEB35K	Brake, Double Electric 7K	
RBSAWT	Tongue, Wrap Around Tongue	
RBTAGN	Gooseneck, Adjustable 2-5/16"	

Prices and specifications subject to change without notice.

